

# master cylinders

1248-H/1260-H 4408 Series Brake Master Cylinders are one of the most frequently specified units in aviation. These rugged units feature virtually trouble-free service, and few wearing parts — provide dependable braking action for a number of general aviation aircraft.

Standard equipment on Piper and other private aircraft for many years, the Brake Master Cylinders are available in the left- and right-hand models required by most aircraft.



AVOX Systems

For Historical Reference Only.


#### **Outstanding Features**

- · Safe, dependable braking action
- Virtually trouble-free performance
- Few wearing parts
- · Left- and right-hand models



#### Specifications

| Displacement                | .80 cu. in. |
|-----------------------------|-------------|
| Maximum working pressure    | 350 lb.     |
| Pedal pressure              | 100 lb.     |
| Recommended hydraulic fluid | MIL-0-5606  |
| Weight as shown             | 21 oz. dry  |
| Maximum Pedal Travel        | 3 3/16 in.  |



#### Parts List

| No. | Part No.  | Name                | No. Req'd |  |
|-----|-----------|---------------------|-----------|--|
| 1   | 1159      | Gasket Vent Screw   | 1         |  |
| 2   | 1220      | Bracket - R.H. Unit | 1         |  |
| 3   | 1232      | Bracket - L.H. Unit | 1         |  |
| 4   | 2003-1    | Pad — Diaphragm     | 1         |  |
| 5   | 1256      | Spring              | 1         |  |
| 6   | 1258      | Screw — Vent        | 1         |  |
| 7   | 2728      | Cover Compression   | 1         |  |
| 8   | 1383      | Piston              | 1         |  |
| 9   | 1712      | Pedal - R.H. Unit   | 1         |  |
| 10  | 1714      | Pedal L.H. Unit     | 1         |  |
| 11  | 2844      | Diaphragm           | 1         |  |
| 12  | 33359-245 | Screw               | 10        |  |
| 13  | 33451-010 | Washer (AN960-10)   | 1         |  |
| 14  | 18431     | Pin — Flat Head     | 1         |  |
| 15  | 18481     | Pin (AN380-2-2)     | 1         |  |


# WARNING

IMPROPER USE OR IMPROPER MAINTENANCE OF THIS EQUIPMENT MAY RESULT IN SERIOUS INJURY OR DEATH. THIS EQUIPMENT IS TO BE SERVICED IN ACCORDANCE WITH APPLICABLE PROCEDURES AND ONLY BY AVOX Systems AUTHORIZED SERVICE TECHNICIANS KNOWLEDGEABLE IN THIS EQUIPMENT. THE NAMES OF AUTHORIZED SERVICE CENTERS ARE AVAILABLE FROM AVOX Systems; OR YOUR AUTHORIZED DISTRIBUTOR.

THE DRAWINGS CONTAINED IN THIS SHEET ARE PRESENTED FOR <u>PART</u>
<u>IDENTIFICATION ONLY</u> AND ARE NOT INTENDED AS AUTHORITY TO PERFORM
ANY TYPE OF SERVICE ON THE EQUIPMENT.

### **Outstanding Features**


- Positive parking brake lock lever
- Safe, dependable braking action
- · Virtually trouble-free performance




## Specifications

| Displacement    | .282 cu. in.         |
|-----------------|----------------------|
| Capacity        | 1.3 cu. in.          |
| Piston Dia.     | .5 in.               |
| Output Pressure | 5.09 x applied force |
| Empty Weight    | 7 oz.                |

#### **Outlet Connections**





#### **Parts List**

| Part No.  | Name   |   |
|-----------|--|---|
| 4008-1    | Piston Clevis Rod (Used on 4408C Master Cyl.)                  |   |
| 4008-2    | Piston Clevis Rod  | 1 |
|           | (Used on Models 4408B1, 4408B2, 4408B3 and 4408B4 Master Cyl.) |   |
| 4014      | Seal — Piston Stem   | 1 |
| 4454      | Cap Reservoir  | 1 |
| 4468-1    | Washer   | 1 |
| 4472      | Cylinder Assembly  | 1 |
| 4472B     | Cylinder Assembly  | 1 |
| 4472C     | Cylinder Assembly  | 1 |
| 4472D     | Cylinder Assembly  | 1 |
| 4473AL    | Reservoir  | 1 |
| 4476      | Piston Assembly  | 1 |
| 4477      | Stem   | 1 |
| 33465-003 | Nut No. 6-32 light hex   | 4 |
| 4479      | Lug — Top Mounting   | 1 |
|           | (Used on Models 4408 and 4408D Master Cyl.)                    |   |
| 4480      | Spring   | 1 |
| 4481      | Nut — Piston Return  | 1 |
| 4482      | Spring — Parking Lock  | 1 |
| 1483      | Stop Piston  | 1 |
| 1484      | Lock — Parking   | 1 |
| 1485      | Spring Washer  | 1 |
| 33473-004 | Nut  | 1 |
| 33551-166 | Rivet  | 1 |
| 33351-020 | Set Screw No. 6-32 x 3/8" long cup point                       | 4 |
| 3332-077  | Screw — Fillister Head 1/4 — 28 x 3/8" long                    | 1 |
| 8037-01   | O-Ring Linear 1820-11  | 1 |
| 8051-00   | U-Cap Linear 1825-43   | 1 |

# For Historical Reference Only.

AVOX Systems Inc. FAA Approved Parts List: Document 3900038

Reference Only Document February 19, 2014



| AVOX System<br>Part Number | s<br>Description         | Approved<br>Replacement For | TC/STC Holder | FAA Approval      | Aircraft Eligibility          |  |
|----------------------------|--------------------------|-----------------------------|---------------|-------------------|-------------------------------|--|
| 1248-H                     | HYDRAULIC PRESSURE UNIT  | 1248-H                      | PIPER         | PMA SUPPLEMENT 20 | PA18 SERIES                   |  |
| 1290H                      | HYDRAULIC PRESSURE UNIT  | 1260H                       | PIPER         | PMA SUPPLEMENT 20 | PA18 SERIES                   |  |
| 4408-00                    | MASTER CYLINDER ASSEMBLY | 4408                        | UNIVAIR       | PMA SUPPLEMENT 62 | STINSON 106-3 (S/N 394) & Up) |  |
| 4408D                      | MASTER CYLINDER ASSEMBLY | 4408D                       | AVIAT         | PMA SUPPLEMENT 64 | CHRISTEN A1                   |  |

